



Accurate, Fast and Reliable

HF MFM

High Flow
Mass Flow Meter



Measurement Range

0 ... 6,12,30,60,120,300 (m³/hr)
Beyond (By Order)



Operating Pressure

Max Inlet Pressure :
10 (bar)
<60 (bar) (By Order)
Min Δ P:
0.5 to 1 (bar)
<0.5 (bar) (By Order)



Operating Gas

Air, N₂, H₂, Ar, O₂
Other Gases (By Order)



HF MFM

High Flow
Mass Flow Meter



Measurement Range

0 ... 6,12,30,60,120,300 (m3/hr)
Beyond (By Order)



Accuracy

$\pm 1.5\%$ (FS)
 $\pm 1\%$ (FS) (By Order)



Response Time

1.5 ... 2.5 (s)
1 ... 1.5 (s) (By Order)



Resolution

500
1000 (By Order)



Turndown

1:50
<1:200 (By Order)



Warm-up time

5 (min) for Acc. $< \pm 2.0$ (FS)
45 (min) for Acc. $< \pm 1.5$ (FS)



Power Supply

20 ... 25 (Volt)



Power Consumption

< 2.8 (Watt)



Electrical Connection

1 x 9 - pin Male Sub-D (DB9)
EX Connector (By Order)




Signal In & Out

0 ... 5 (Volt)
4 ... 20 (mA) (By Order)
Modbus (By Order)
(RS485_Auto Baud Rate)
(RTU_ASCII)



Operating Gas

Air, N₂, H₂, Ar, O₂
Other Gases (By Order)



Operating Temperature

-5 ... +70 (°C)




Operating Pressure

Max Inlet Pressure :
10 (bar)
<60 (bar) (By Order)
Min ΔP:
0.5 to 1 (bar)
<0.5 (bar) (By Order)



Wet Parts

SS 304 & AI
SS 316 & CRC* (By Order)



Seals

NBR
Viton, EPDM, FVMQ (By Order)



Mechanical Fitting

BSP: 1/4" - 3/8" - 1/2" - 1"
Flange: 1/2" - 1" - 1.5" - 2"
Other (By Order)



Dimensions

A*: 70x32x133 (mm)
B*: 120x49x161 (mm)
C*: 180x79x190 (mm)



Weight

A*: ~500 (gr)
B*: ~600 (gr)
C*: ~1900 (gr)

* CRC: Corrosion Resistant Coating Part

* A: Up to 12 (m3/hr) with BSP_SS 304

* B: Up to 60 (m3/hr) with BSP_AI

* C: Above 60 (m3/hr) with BSP_AI