

Accurate, Fast and Reliable

HP MFC

High Pressure

Mass Flow Controller







Measurement Range

0 ... 10,20,50,100,200,500 (sccm) 0 ... 1,2,5,10,20,50 (slm) Other Range up to 50slm (By Order)



Operating Pressure

Max Inlet Pressure: <40 (bar) <100 (bar) (By Order) Max ΔP:

15 (bar)

<25 (bar) (By Order)

Min ΔP:

1 (bar)

<1 (bar) (By Order)



Operating Gas

Air, N2, H2, Ar, O2 Other Gases (By Order)



HP MFC

High Pressure

Mass Flow Controller





Measurement Range

0 ... 10,20,50,100,200,500 (sccm) 0 ... 1,2,5,10,20,50 (slm) Other Range up to 50slm (By Order)



Accuracy

< ± 1.5% (FS) < ± 1% (FS) (By Order)



Response Time

1.5 ... 2.5 (s) 1 ... 1.5 (s) (By Order)



Resolution

500 1000 (By Order)



Turndown

1:50 1:100 (By Order)



Warm-up time

5 (min) for Acc. < ±2.0 (FS) 45 (min) for Acc. < ±1.5 (FS)



Power Supply

20 ... 25 (Volt)



Power Consumption

< 7.2 (Watt)



Electrical Connection

1 x 9 - pin Male Sub-D (DB9) EX Connecter (By Order)



Signal In & Out

0 ... 5 (Volt) 4 ... 20 (mA) (By Order) Modbus (By Order) (RS485_Auto Baud Rate) (RTU ASCII)



Operating Gas

Air, N2, H2, Ar, O2 Other Gases (By Order)



Operating Temperature

-5 ... +40 (°C)





/lax Inlet Pressure : <40 (bar) <100 (bar) (By Order)

Max ΔP: 15 (bar)

<25 (bar) (By Order) Min ΔP: 1 (bar)

1 (bar) <1 (bar) (By Order)



Wet Parts

SS 304 & SS 420 & AI SS 316 & CRC* (By Order)



Seals

NBR Viton, EPDM, FVMQ (By Order)



Mechanical Fitting

BSP: 1/4" Other (By Order)



Dimensions

98x40x133 (mm)



Weight

~800 (gr)



Accurate, Fast and Reliable

HP MFC

High Pressure

Mass Flow Controller







Measurement Range بازهاندازه گیری

0 ... 10,20,50,100,200,500 (sccm) 0 ... 1,2,5,10,20,50 (slm) Other Range up to 50slm (By Order)



Operating Pressure فشار کاری

Max Inlet Pressure : <40 (bar) <100 (bar) (By Order) Max ΔP: 15 (bar)

<25 (bar) (By Order) Min ΔP:

1 (bar)

<1 (bar) (By Order)



Operating Gas

گاز کاری

Air, N2, H2, Ar, O2 Other Gases (By Order)